

DESCRIPTION

STABOND SWD 1000 is a fast drying, primer intended for spray application.

PROPERTIES

TYPE:	SYNTHETIC ELASTOMER	THINNER:	STABOND "T" THINNER
COLOR:	BLACK	SOLIDS:	10%
VISCOSITY:	25 CPS	WT/GAL:	6.4 LBS
SHELF LIFE:	6 MONTHS	APPLICATION TEMP.:	70° F TO 100° F
FLAMMABLE:	YES	PEEL STRENGTH:	≥ 18 PIW

APPLICATION

Apply primer with 1.5 or 2 cross coats (3 or 4 passes) allowing it to dry between passes. Ensure that the primer is dry before proceeding with processing of the primed part.

STORAGE

For maximum shelf life, store material in cool dry area and keep container tightly sealed. Storage temperature of 60° -80° F. are recommended. Lower storage temperature will cause a temporary increase in viscosity. Rotate stock on a "First in First out" basis.

DANGER

Extremely flammable. Toxic. Vapors may ignite explosively. Provide fresh air cross ventilation to prevent build-up of vapors. Keep away from heat, sparks and from open flame. Do not smoke. Extinguish all flames and pilot lights and turn off all non-explosion proof electrical equipment and sources of ignition during use and until vapors are dissipated. Avoid prolonged or repeated breathing of vapors. Close container after use. Contains aliphatic hydrocarbons. **KEEP OUT OF REACH OF CHILDREN.** Harmful or fatal if swallowed. If swallowed do not induce vomiting, seek immediate medical attention. THOROUGHLY READ THE SDS FOR THIS PRODUCT PRIOR TO USING IT.

IMPORTANT

Suggestions for the use of this product are based on tests believed to be reliable; however, the user should determine suitability for the intended use by his own evaluation. Because the use of the material is beyond our control, neither the seller nor the manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use or inability to use this product. Seller and manufacturer's sole obligation shall be replacement of material proved to be defective.